




60kW

Dual Gun | CCS-2

Dynamic Power Sharing



**Engineered for extreme Indian conditions,
delivering 3% higher energy efficiency**



Higher RoI

Annual incremental margin of approx. ₹1.3 lacs for a 60KW DC charger



Higher De-rating Temperature

Operates at up to **55°C ambient temperature** without derating, ensuring **higher uptime**



Intelligent Remote Monitoring

Maximum uptime, faster service, and **lower operating costs** for the customer



Auto-Charge Enabled

OCPP 1.6J & 2.0.1 compliant, with **Auto-Charge** functionality



Rapid Customization

In-house firmware and manufacturing - faster feature and design development



Faster Spares & Service

Field engineers across 40 cities & in-house hardware + software stack – ensuring **faster spares availability (<72 hrs)**

Zenergize vs IGBT Based Fast Charger

Product Feature	Zenergize	Competition Chargers
Remote Health & Performance Monitoring	YES – Smart HMPU	Maybe/ No
Technology	SiC MOSFET	IGBT
Efficiency	≥96.6%	≥94%
De-rating Temperatures	55°C	45°C
Power Module	In-house designed and manufactured	Imported
Firmware	In-house	Outsourced

60kW Product Specifications

Parameters	Rating	Specification
Input Parameters	Input Voltage Type	415V Three Phase, 5 Wire (R, Y, B, N, PE)
	T.H.D (i)	<2% at rated load
	Power Factor	>0.99 (at rated load) and >0.98 (with load >50% rated load)
	Maximum Input Current	100A rms (per phase)
Output Parameters	Number of Guns	2
	Output Voltage Range	100-1000 Vdc
	Maximum Output Current (per gun)	200A
	Power Conversion Efficiency	> 96.6% (at rated load and 800 Vdc output)
	Dynamic Power Sharing	Yes
Interface and Control Functions	Display Screen (HMI)	10" TFT Touch Screen
	User Authentication	Using mobile application or HMI: QR Code / RFID Card / Password Login
	Input AC energy meter	Yes
	Battery Backup	30 minutes
Communication	Between EV and EVSE	Low Level Communication as per IEC 61851-1, High Level Communication as per DIN SPEC 70121 and ISO 15118
	Between EVSE and CMS	OCPP 1.6J and OCPP 2.0.1 software protocols via WiFi/ GSM (2G/3G/4G)/Ethernet
Mechanical	Ingress Protection	IP55
	Cooling	Forced Air Cooling
	Charging Cable Length	5 m (optional up to 7m available)
	Operating Temperature	-25°C to 75°C (de-rating > 55°C)
	Weight	220 Kg (With Power module)
	Dimensions (HxWxD) in mm	1350x850x749
	Material	Phosphated mild steel with powder coating or Stainless Steel

Zenergize

Delta Tower, 3rd floor, Plot No. 54, Sector 44,
Gurugram, Haryana - 122003

Email: contact@zenergize.in
Website: zenergize.in

Phone: +91 99587 88932